




407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B
- Other means of identification:**
- UFI:** 78X4-C0AN-Q00P-KK8C
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- Relevant uses: Industrial paint. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
- EUPINCA
C/ Londres, 13 - Pol. Ind. Cabezo Beaza
30353 Cartagena - Murcia - España
Phone: +34 968089000
info@grupotkrom.com
<https://www.tkrom.com/>
- 1.4 Emergency telephone number:** +34 968 08 90 00 (Oficce hours)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
- Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
- Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
- Warning**
- 
- Hazard statements:**
- Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.
 P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Substances that contribute to the classification

Hexamethylene diisocyanate, oligomers; Hydrocarbons, C9, aromatics; Reaction mass of ethylbenzene and m-xylene and p-xylene

Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate⁽¹⁾ ATP ATP01		25 - <50 %
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	
CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17-XXXX	Hexamethylene diisocyanate, oligomers⁽²⁾ Self-classified		25 - <50 %
	Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	
CAS: 128601-23-0 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics⁽²⁾ Self-classified		10 - <25 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	
CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-2119455267-33-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene⁽²⁾ Self-classified		10 - <25 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	

⁽¹⁾ Substance with a Union workplace exposure limit

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
	LD50 oral	Not relevant	
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral	Not relevant	
CAS: Non-applicable	LD50 dermal	1100 mg/kg	Rat
EC: 905-562-9	LC50 inhalation	11 mg/L (ATEI)	
Hexamethylene diisocyanate, oligomers	LD50 oral	Not relevant	
CAS: 28182-81-2	LD50 dermal	Not relevant	
EC: 931-274-8	LC50 inhalation	11 mg/L (ATEI)	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -

**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B****SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:**A.- Specific storage requirements**

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE -



**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	50 ppm	275 mg/m ³
2-methoxy-1-methylethyl acetate ⁽¹⁾ CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³

⁽¹⁾ Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	796 mg/kg	Not relevant
	Inhalation	Not relevant	550 mg/m ³	275 mg/m ³	Not relevant
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	1 mg/m ³	Not relevant	0,5 mg/m ³
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	150 mg/m ³	Not relevant
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	Not relevant	36 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	320 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	33 mg/m ³	33 mg/m ³
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	11 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	11 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	32 mg/m ³	Not relevant
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³

PNEC:

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L	
	Soil	0,29 mg/kg	Marine water	0,064 mg/L	
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,329 mg/kg	
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	STP	88 mg/L	Fresh water	0,127 mg/L	
	Soil	53183 mg/kg	Marine water	0,013 mg/L	
	Intermittent	1,27 mg/L	Sediment (Fresh water)	266701 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	26670 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg	

- CONTINUED ON NEXT PAGE -

407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 74,51 % weight


**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. density at 20 °C:	710,94 kg/m ³ (710,94 g/L)
Average carbon number:	7,52
Average molecular weight:	120,64 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	Colourless
Odour:	Not available
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	148 °C
Vapour pressure at 20 °C:	453 Pa
Vapour pressure at 50 °C:	2644,19 Pa (2,64 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	954,2 kg/m ³
Relative density at 20 °C:	0,954
Dynamic viscosity at 20 °C:	3000 cP
Kinematic viscosity at 20 °C:	3144,03 mm ² /s
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	37 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:
Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *
Other safety characteristics:	
Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -


**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**
SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Organs affected: All gross lesions and masses.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	8532 mg/kg		Rat
		5100 mg/kg	Rat
		30 mg/L (4 h)	Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	2100 mg/kg		Rat
		1100 mg/kg (ATEI)	Rat
		11 mg/L (ATEI)	
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	5100 mg/kg		Rat
		11 mg/L (ATEI)	

11.2 Information on other hazards:
Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:
Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	161 mg/L (96 h)		Pimephales promelas	Fish
		481 mg/L (48 h)	Daphnia sp.	Crustacean
		Not relevant		

- CONTINUED ON NEXT PAGE -

**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
	LC50	EC50		
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	LC50	Not relevant		
	EC50	Not relevant		
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	EC50		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Not relevant	785 mg/L	8 days
	COD	Not relevant		
	BOD5/COD	Not relevant	% Biodegradable	100 %
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	Pow Log
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BCF	9
	Pow Log	2.77
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Conclusion	Henry	Dry soil
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- CONTINUED ON NEXT PAGE -



**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):



**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety

- CONTINUED ON NEXT PAGE -



407200002 - CATALIZADOR POLIURETANO 2C ESMALTE ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B

SECTION 15: REGULATORY INFORMATION (continued)

— certification or documented proof that training has been successfully completed

(b) intermediate level training, including on-line training, on:

— additional behaviour-based aspects

— maintenance

— management of change

— evaluation of existing safety instructions

— risk in relation to application process used

— certification or documented proof that training has been successfully completed

(c) advanced training, including on-line training, on:

— any additional certification needed for the specific uses covered

— spraying outside a spraying booth

— open handling of hot or warm formulations (> 45 °C)

— certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law

(b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates

(c) national exposure limits for diisocyanates, if there are any

(d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

H332: Harmful if inhaled.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

- CONTINUED ON NEXT PAGE -



**407200002 - CATALIZADOR POLIURETANO 2C ESMALTE
ANTIOXIDANTE FORJA BRILLO STI COMPONENTE B**

SECTION 16: OTHER INFORMATION (continued)

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Sens. 1: Calculation method

STOT SE 3: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Acute Tox. 4: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -